

CASE NO.: 50T5573.01  
Serial No.: 10/616,669  
October 20, 2004  
Page 2

PATENT  
Filed: July 10, 2003

1. (currently amended) A raster-type display, comprising:  
a landing correction coil;  
a current source coupled to the landing correction coil and outputting a landing misalignment correction signal thereto; and  
at least one sensor generating a control signal, the control signal being sent to the current source to establish the landing misalignment correction signal at least partially based thereon, ~~the landing misalignment correction signal being representative of at least one of: temperature, ambient magnetic field, and pressure, wherein the sensor is at least one of: a temperature sensor, and a magnetic sensor, and the landing misalignment correction signal is a ramp signal.~~
2. (original) The display of Claim 1, wherein the landing correction coil is disposed at a location of the display wherein electron beams for respective activation of red, green, and blue display elements converge
3. (original) The display of Claim 2, wherein the display contains no other landing correction coils apart from the landing correction coil, the landing correction coil also carrying a speed correction signal.
4. (original) The display of Claim 2, wherein the current source receives a position signal for establishing an amplitude of the landing misalignment signal at least partially based on a position of an electron beam of the display.

1166-83.AM10

CASE NO.: 50T5573.01  
Serial No.: 10/616,669  
October 20, 2004  
Page 3

PATENT  
Filed: July 10, 2003

5. (original) The display of Claim 4, wherein the control signal is a DC signal.
6. (original) The display of Claim 5, wherein the current source comprises a member receiving the control signal and converting the control signal to the time varying landing misalignment correction signal.
7. (original) The display of Claim 6, wherein the member receives a time varying signal from a horizontal drive circuit of the display.
8. (canceled).
9. (canceled).
10. (original) The display of Claim 2, further comprising a velocity modulation (VM) coil.
11. (original) The display of Claim 10, wherein the VM coil and the landing correction coil both receive signals for correcting for electron beam misalignment.
12. (currently amended) A method for correcting for electron beam landing misalignment in a raster-type display, comprising:

1168-89.AMD

CASE NO.: 50T5573.01  
Serial No.: 10/616,669  
October 20, 2004  
Page 4

PATENT  
Filed: July 10, 2003

applying an alignment correction signal to a coil located at a convergence of three beams of the display, the alignment correction signal being established to correct for landing offset of the beams caused by ~~at least one of: temperature effects, magnetic field effects, and pressure effects,~~ wherein the alignment correction signal being a sinusoid.

13. (original) The method of Claim 12, wherein the coil is a VM coil carrying a speed correction signal.

14. (original) The method of Claim 12, comprising providing:  
a current source coupled to the coil and outputting a landing misalignment correction signal thereto; and

at least one sensor generating a control signal, the control signal being sent to the current source to establish the landing misalignment correction signal based at least partially thereon.

15. (original) The method of Claim 12, wherein the display includes a velocity modulation (VM) coil and the method includes applying signals for correcting for electron beam misalignment to the VM coil and the landing correction coil.

16. (original) The method of Claim 12, comprising applying a vertical position signal for establishing an amplitude of the landing misalignment signal at least partially based on a vertical position of an electron beam of the display.

1163-89.AMD

CASE NO.: 50T5573.01  
Serial No.: 10/616,669  
October 20, 2004  
Page 5

PATENT  
Filed: July 10, 2003

17. (original) The method of Claim 16, wherein the control signal is a DC signal and the current source comprises a switch receiving the control signal and converting the control signal to the time varying landing misalignment correction signal.

18. (currently amended) A raster display, comprising:

single coil means for influencing at least scanning one electron beam for undertaking landing misalignment correction of the beam

a current source means coupled to the single coil means for outputting a landing misalignment correction signal thereto; and

at least one sensing means for generating a control signal, the control signal being sent to the current source means to establish the landing misalignment correction signal at least partially based thereon, the signal being representative of at least one of: temperature, ambient magnetic field, in which case the correction signal is a ramp signal, or pressure, in which case the correction signal is a sinusoid.

19. (canceled).

20. (currently amended) The display of Claim [19]18, wherein the current source means receives a vertical position signal for establishing an amplitude of the landing misalignment signal at least partially based on a vertical position of the scanning electron beam.

11/02/04.AMD

CASE NO.: 50T5573.01  
Serial No.: 10/616,669  
October 20, 2004  
Page 6

PATENT  
Filed: July 10, 2003

21. (currently amended) The display of Claim [19]18, wherein the control signal is a DC signal.

22. (original) The display of Claim 21, wherein the current source means comprises switch means for receiving the control signal and converting the control signal to the landing misalignment correction signal.

23. (currently amended) The display of Claim [19]18, wherein the switch means receives a time varying signal from a horizontal drive circuit.

24. (currently amended) The display of Claim [19]18, the single coil means also carrying a speed correction signal.

1168-89.AMD